

## Compare MINELAB GPX 5000 GPX 4800 and GPX 4500 Specifications

Product	GPX 5000	GPX 4800	GPX 4500
<b>Application</b>	Gold Prospecting & Deep Relic	Gold Prospecting & Deep Relic	Gold Prospecting & Deep Relic
<b>Technology</b>	MPS, DVT & SETA	MPS, DVT & SETA	MPS, DVT & SETA
<b>Frequency/Transmission</b>	Bi-Level, Advanced Pulse Induction	Bi-Level, Advanced Pulse Induction	Bi-Level, Advanced Pulse Induction
<b>Coil (standard)</b>	11" Round Double-D plus 11" Monoloop.	11" Round Double-D.	11" Round Double-D.
<b>Audio Output</b>	6.35mm (1/4") headphone/speaker jack.	6.35mm (1/4") headphone/speaker jack.	6.35mm (1/4") headphone/speaker jack.
<b>Headphones Supplied</b>	Koss 100 ohm headphones.	Koss 100 ohm headphones.	Koss 100 ohm headphones.
<b>Visual Display</b>	64 x 128 pixels, transfective with white backlight.	64 x 128 pixels, transfective with white backlight.	LCD screen 64x128 pixels, transfective.
<b>Backlight</b>	Yes with adjustable automatic 'time-out'.	Yes with adjustable automatic 'time-out'.	Yes with adjustable automatic 'time-out'.
<b>USB Connectivity</b>	-	-	-
<b>Memory</b>	Setting changes saved automatically and remain until changed or reset. Factory Presets can be restored on start-up.	Setting changes saved automatically and remain until changed or reset. Factory Presets can be restored on start-up.	Setting changes saved automatically and remain until changed or reset. Factory Presets can be restored on start-up.
<b>Depth Indication</b>	-	-	-
<b>Detect Modes</b>	General, Deep, Hi-Mineral, Patch, Hi-Trash & Pinpoint (all user programmable)	General, Deep & Hi-Mineral (all user programmable)	General, Deep & Custom. Custom Modes are: Hi Mineral, Hi Trash, Patch & Test A.
<b>Discrimination</b>	Iron Reject: range 1 to 10 & Off (All Metal).	Iron Reject: range 1 to 10 & Off (All Metal).	Iron Reject: range 1 to 10 Off & All Metal.
<b>Timings</b>	Normal, Sensitive Extra, Enhance, Sharp, Sensitive Smooth, Coin/Relic, Salt/Gold & Fine Gold.	Normal, Sensitive Extra, Enhance, Sharp, Coin/Relic & Salt-Coarse	Enhance, Normal, Sensitive Smooth, Salt Course, Sensitive Extra & Sharp.
<b>Audio tone</b>	Variable Control 1 to 100.	Variable Control 1 to 100.	Variable Control 1 to 100.
<b>Audio Type</b>	Quiet, Normal, Deep & Boost.	Quiet, Normal & Deep.	Quiet, Normal, Deep & Boost.
<b>Ground Balance</b>	Automatic Ground Balance, Fixed & Tracking: Slow, Medium & Fast. Quick-Trak button.	Automatic Ground Balance, Fixed & Tracking: Slow, Medium & Fast. Quick-Trak button.	Automatic Ground Balance, Fixed & Tracking: Slow, Medium & Fast.

## Compare MINELAB GPX 5000 GPX 4800 and GPX 4500 Specifications

Product	GPX 5000	GPX 4800	GPX 4500
<b>Ground Balance Type</b>	General, Specific & Ground Balance Off.	General & Ground Balance Off.	General, Specific & Ground Balance Off.
<b>Trash Density</b>	-	-	-
<b>Pinpoint</b>	-	-	Quick-Trak button.
<b>Sensitivity Adjust</b>	Rx Gain 1 to 20.	Rx Gain 1 to 15.	Rx Gain 1 to 15.
<b>Tune / Noise Cancel</b>	Automatic & Manual 0 to 255.	Automatic & Manual 0 to 255.	Automatic & Manual 0 to 255.
<b>Threshold</b>	Adjustable turn control.	Adjustable turn control.	Adjustable turn control.
<b>Target Volume Adjust</b>	Target Volume 1 to 20. Volume Limit 1 to 20.	Target Volume 1 to 20. Volume Limit 1 to 20.	Volume Limit 1 to 20.
<b>Battery</b>	Lithium-ion rechargeable battery 68Wh with in-built amplifier for speaker use. Approx. 12 Hours use. Supplied with mains and vehicle charger.	Lithium-ion rechargeable battery 68Wh with in-built amplifier for speaker use. Approx. 12 Hours use. Supplied with mains and vehicle charger.	Lithium-Ion with built-in amplifier (up to 12 hrs). Supplied with mains and vehicle charger.
<b>Low battery alert</b>	Audio alert.	Audio alert.	Audio alert.
<b>Length</b>	1100mm (43.3") to 1300mm (51.2").	1100mm (43.3") to 1300mm (51.2").	1100mm - 1300mm (43.3" - 51.2").
<b>Weight</b>	2.4kg (5.3lbs) including 11" coil (excluding battery and accessories). Battery weight 780g (1.7lbs).	2.4kg (5.3lbs) including 11" coil (excluding battery and accessories). Battery weight 780g (1.7lbs).	2.4kg (5.3lbs) (ex. battery).
<b>Warranty</b>	3 years control box & coil.	3 years control box & coil.	3 years control box & coil.

<b>Highlighted Cells</b>	Yellow Highlighted cells show the main differences
--------------------------	--